

# Depth Filter

## FFP, MFP, SMFP


The silicone free depth filter for the removal of water and oil aerosols as well as solid particles from compressed air and gases with absolute retention efficiency.

### Product description:

The silicone free depth filter employs a three dimensional micro fibre fleece made out of binderfree glassfibre. A prefilter medium 1 µm is integrated and realises an effective two stage filtration.

### Characteristics:

By utilising various filtration mechanisms such as retention by direct impact, sieve effect and diffusion effect, liquid aerosols and solid particles down to the size of 0.01 µm are being retained in the filter.



Cross section of the depth filter

### Applications:

The depth filter is for example being utilised in the following industries:

- Automobile industry (applications of lacquer finishes)
- Chemical industry
- Petrochemical industry
- Pharmaceutical industry
- Plastic industry
- General machine fabrication
- Air conditioning technology
- Food industry
- Paint industry
- Beverage industry
- Process industry for instrumentation and control air

## Depth Filter FFP, MFP, SMFP

Features:	Benefits:
Expanded inner and outer stainless steel sleeves for the secure hold of the filter medium	No danger of corrosion - large openings ensure low differential pressure drop and high throughput
Binderfree depth filter medium made out of borosilicate glass fibres	Low differential pressure drop; high throughput
Removal of liquid aerosols and solid particles down to 0.01 µm	Validated retention efficiency, high level of security and safety
Large surface area, large void volume (> 94%)	High dirt holding capacity; guaranteed service life time

Materials:	
Support sleeves - inner and outer	Stainless steel 1.4301/304
Pre-and after filter medium	Cerex®
Filter medium	Binderfree borosilicate
Bonding	Polyurethane
End caps	Aluminium (for HT/ NX: stainless steel)
2 O-Rings	Viton, labs-free

Validation:
Validation of high-efficiency filters by Technical University Dresden

Retention rate related to particles 0,01 µm:	
FFP =	99.999%
MFP =	99.99998%
SMFP =	99.99999%

Residual oil content at an inlet concentration of 3mg/ m <sup>3</sup>	
FFP =	0.1 mg/ m <sup>3</sup>
MFP =	0.03 mg/ m <sup>3</sup>
SMFP =	< 0.01 mg/ m <sup>3</sup>

Max. differential pressure:
5 bar at 20°C, irrespective of system pressure

Initial differential pressure at nominal flow:	
FFP =	0.05 bar
MFP =	0.08 bar
SMFP =	0.12 bar

Element type	Correction factor Filter surface KF
02/05	0.08
03/05	0.10
03/10	0.12
04/10	0.17
04/20	0.19
05/20	0.25
05/25	0.32
07/25	0.47
07/30	0.68
10/30	1.0
15/30	1.55
20/30	2.10
30/30	3.20
30/50	5.65

### Performance of FFP, MFP, SMFP elements - compressed air

